



Installation Instructions

Tow Hook p/n's 13200, 13230

As you read these instructions, you will see **NOTES**, **CAUTIONS** and **WARNINGS**. Each message has a specific purpose. **NOTES** are additional information to help you complete a procedure. **CAUTIONS** are safety messages that indicate a potentially hazardous situation which, if not avoided, may result in minor or moderate injury. A **CAUTION** may also be used to alert against unsafe practice. **WARNINGS** are safety messages that indicate a potentially hazardous situation, which, if not avoided could result in serious injury. **CAUTIONS** and **WARNINGS** identify the hazard, indicate how to avoid the hazard, and advise of the probable consequence of not avoiding the hazard. **PLEASE WORK SAFELY!**

WARNING

To Prevent Serious Injury :

- Keep all persons safely away from both vehicles and connecting rigging
- Do not exceed the rating of the rigging being used
- The anchor point on the other vehicle must be capable withstanding stress beyond the pull
- If the attaching point were to break when using these items, they could recoil with immense force
- Weak anchor points can break, possibly causing property damage or physical injury due to the recoil of the attaching system

1. Pick a desirable location to attach the Warn Tow Hook. This location may be on the vehicle frame, front or rear bumper, Warn Winch Mounting Bracket, etc. (**NOTE:** Some competitive winch mounting kits may not have sufficient strength to support heavy loads).

CAUTION: To prevent personal injury or vehicle damage, the location you choose must be capable of supporting at least 10,000 pounds of force.

2. When you have chosen the location for the Warn Tow Hook, place it in the desired position and mark the two holes for drilling.
3. Drill two 9/16" (.5625) dia. or 14mm dia. holes at the places marked.
4. Align the holes in the Tow Hook with the drilled holes and insert the two 1/2-13 x 2 " hex cap screws. Secure with lockwashers and hex nuts.

CAUTION: If for any reason you replace the capscrews with longer or shorter ones, they must be 1/2-13, grade 5 or 8. **DO NOT USE STANDARD GRADE 2 CAPSCREWS.**

5. Tighten capscrews to 75 lb./ft., 10.3kg./m.
6. Your Tow Hook is now ready for use when you need it. Thank you for purchasing it from Warn Industries.

WARN TOW HOOK

90 DAY LIMITED WARRANTY STATEMENT

Warn Industries warrants each new Warn Accessory specified above against factory defects in material and workmanship for 90 days after date of purchase. The owner will be responsible for returning any defective items, transportation costs prepaid, to Warn Industries Service Department or factory authorized servicing distributor. Warn Industries will, without charge, repair or replace, at its option, accessories or accessory parts which its inspection determines to be defective. Such items will be returned with transportation costs prepaid from the service point. A copy of the purchaser's receipt must be returned with the defective items to verify the warranty period. Exclusions from this warranty are the finish and any conditions determined by Warn Industries to have been caused by abnormal use or service.

There are no warranties, expressed or implied (including any implied warranties of merchantability and fitness), which extend beyond this warranty period. The loss of this product, loss of time, inconvenience, commercial loss or consequential damages are not covered. Warn Industries reserves the right to change the design of any product without assuming any obligation to modify any product previously manufactured.

This warranty gives you specific legal rights. You may also have other rights which may vary from state to state. Some states do not allow the limitations on how long an implied warranty lasts. Some states do not allow the exclusion or limitation of incidental or consequential damages. Therefore, the above limitations may not apply to you.

Products specified above returned for warranty service should be sent to:

**WARN INDUSTRIES
Service Department
12900 S.E. Capps Road
Clackamas, OR 97015
1-800-543-WARN**