



Protecting Your Adventure Lifestyle

Warrior Products, Inc.
16850 SW Upper Boones Ferry Rd
Ste. A
Durham, OR 97224
Phone (888) 220-6861
Fax (503) 692-0364
sales@warriorproducts.com

BREEZER TOP INSTALLATION INSTRUCTIONS WAR 1165 & 1170 JK WRANGLER

NOTE: The Warrior Breezer Top requires the use of the Bestop Quick Detach Windshield Header, part number 51243-01. It is not known to fit with any other brand of channel.

Installation:

1. In the rear corners of your Jeep, pull back the carpet and find an adequate spot on the inner tub wall to mount the two black footman loops. Position the footman loops in the same location relative to each corner so that the straps will be even from side to side. Begin with the driver side first. You should be able to position it so that the strap of the Breezer Top will slide through the existing slot in the carpet where your hard top wiring normally passes through. Position the passenger side to match the driver side. You can choose to cut a matching slot in that side of the carpet as well or just run the strap between the carpet and the edge of the tub.
2. With the locations of your footman loops chosen. Mark the mounting holes with a felt marker or scribe and center punch the marks. Drill all 4 marks with a 1/8" drill bit. Use a screwdriver to fasten the loops into place. These will be a permanent modification as they'll be hidden behind the carpet when not in use.
3. Using the proper sized Torx driver, remove the 8 screws that fasten the header knob bases to the Bestop Quick Detach Windshield Header. Snap the Warrior Breezer Top onto the existing snaps located on the windshield header.
4. Position the header knob bases back onto the windshield header and note where the screw holes are located. Using a utility knife or similar tool, make small slits through the breezer material where the screws will go. Reinstall the header knob bases sandwiching the breezer material between the bases and the windshield header.
5. Roughly position the top into place. Position the windshield channel into place and latch it into place.
6. Begin cinching down the straps around the roll bar, speaker bar, and to the footman loops you already installed. It works best to get all of the straps into place, then work your way around the Jeep cinching them all tight. Tuck in any hanging strap ends.
7. This completes your Breezer Top installation. To uninstall, simply unhook all of the straps and the windshield channel, roll the Breezer Top up around the channel, and store it away.

If you need further assistance installing your product, please contact us by email at techsupport@warriorproducts.com or call us at (888) 220-6861.

THANK YOU FOR PURCHASING WARRIOR PRODUCTS

QUALITY • INTEGRITY • INNOVATION • SERVICE