



Protecting Your Adventure Lifestyle

Warrior Products, Inc.
16850 SW Upper Boones Ferry Rd
Ste. A
Durham, OR 97224
Phone (888) 220-6861
Fax (503) 692-0364
sales@warriorproducts.com

Generic LED Corner **Installation Instructions**

All corners are designed to be placed over the existing factory metal body. During shipping and handling your aluminum corners may be slightly altered but diamond plate aluminum is easy to flex and bend back into proper form. Make any slight modifications needed to enhance their fit. Also, because all body tubs are not built the same, some small modifications to the Corners may be required for a proper fit.

Rivets are supplied for mounting your corners to the body tub. If you prefer, you can use self tapping screws (not provided). Installation does not require the use of any sealant, but you may utilize some silicone to seal your corners to the body if you prefer. We highly recommend spraying any exposed metal with primer before installing your Corners to keep rust from becoming a problem later.

Corners are designed for use with our part #2917 LED Tail Light & Reverse Light Kit, which includes standard grommet mounted 4" Tail Lights and 2" Reverse Lights.

Installation:

1. Remove all tail lights, side markers, the gas tank rubber filler housing, and any other items that may be in the way of the installation process. 97 and newer models do not require the gas tank filler plastic removed, as the corner is designed to fit over the plastic filler surround.
2. Hold your Corners in place and mark the two round holes for your LED Tail Light Cutouts.
3. Once the holes are marked on your Jeep, set the corners aside and cut out the holes. When cutting these, you can start the process by drilling starter holes and then use a metal bladed saw to make the cuts. It is recommended to cut the hole slightly larger (approximately 1/8" greater diameter) than the hole in the LED Corner for better grommet fitment.
4. Once the holes are cut, you may want to use a die grinder with a carbide bit or stone to deburr and smooth the edge. Finish by painting the exposed metal with primer. On the '07 and later JK Wrangler model, you will also need to drill a hole on the passenger side so that the reverse light grommet can get from the tail light area over to the reverse light area, as there is a single layer body panel that blocks access.
5. You can now begin installing the corners. You will need a 3/16" drill bit, a drill and a pop-rivet tool.
6. Once you've got all of your rivets securely attached and the corners are on the vehicle securely, you can re-assemble any parts removed in step #1 that need to go back onto your Jeep.
7. Note: On some TJ models you will find a fuel evap canister that interferes with installing the passenger tail light. You will need to relocate this box slightly in order to install the tail light. The simplest relocation is to loosen it and just slightly move it forward. You should be able to get most of the bolts reinstalled with this method.
8. The last part of the installation is to install your tail lights. If you've chosen to use our light kit, begin by wiring our tail light and reverse light pigtailed into your factory wiring on the vehicle. Wire to wire will vary on the vehicle, so some testing will need to be done to identify which wires you will be using. Our light grommets simply press into place in the holes you've cut. The LED light kits will include a wiring help document that you can reference for assistance.
9. Once the wiring is complete and the grommets are in place, plug your lights into the pigtailed and then test to make sure they are working. The reverse lights pigtail can be flipped so if it is not working, try spinning the plug before attempting to backtrack any other wiring errors.
10. With the taillights and reverse lights working, pop them into place by pushing them evenly into the grommets. This will complete your installation.

Thank you for purchasing Warrior Products!

QUALITY • INTEGRITY • INNOVATION • SERVICE